

Technical Data Sheet

WESSCO® POLAR 29.419.30 UV Silver Premium Bright

UV premium silver for finishing of printed products. Suitable for flexo units. Low viscosity.

ACTEGA Schmid Rhyner AG

Soodring 29, 8134 Adliswil, CH

+41 44 712 64 00

info.ACTEGA.SchmidRhyner@altana.com

www.actega.com

Product Description

UV curing under atmospheric conditions.

Low migration, suitable for the outside of food and other sensitive packaging, in compliance with legal requirements and guidelines (GMP).

General Information	
Product Type	Inks
Product Technology	UV curing
tds_label_fieldOfApplication	Labels, Pressure Sensitive Labels
Colors	prd_color_metallicSilver, prd_color_silverPremiumBright
Optic	•

Application Method

- Flexo unit
- Stir well before use !
- The property profile of the coating film is given in case of a complete curing. The curing depends on the efficiency of lamps, life of UV lamps, machinery speed, general conditions of the UV unit (reflectors, etc.), temperature and the distance from the UV unit to the substrate. We recommend to clean regularly the reflectors and - if necessary - to change the lamps in case of a drop in lamp efficiency.
- A strong absorption on absorbent surfaces can cause an insufficient curing of the UV varnish, sensory problems, mechanical influence as well as rub resistance problems and poor slip properties.
- The total structure of substrate/printing ink/varnish must be cured sufficiently before processing and should be checked during the process.
- The increase of the slip angle can't be excluded in case of temperature and humidity. Storage tests are necessary.
- Suitable for Flexographic printing

Printing Equipment and Anilox Recommendation	
Printing Equipment	Anilox Volume
Open-cell anilox, such as GTT, HIT, Haschur, or ART, with a maximum line count of 80 L/cm to avoid thickening.	6-15 cm ³ /m ² / 0-0 ft ³ /ft ²

Substrate Recommendation

- various films and paper

Technical Data Sheet

WESSCO® POLAR 29.419.30 UV Silver Premium Bright

UV premium silver for finishing of printed products. Suitable for flexo units. Low viscosity.

ACTEGA Schmid Rhyner AG

Soodring 29, 8134 Adliswil, CH

+41 44 712 64 00

info.ACTEGA.SchmidRhyner@altana.com

www.actega.com

Product Characteristics			
Viscosity	• ~250 mPas + / - 150 (mPa*s at 23°C)		
Benzophenone free	<input type="checkbox"/>	Glueability	<input type="checkbox"/>

Storage Instructions

- Shelf-life 6 months
- Storage at temperatur between 5°C and 35°C
- Protect from frost, heat and sun exposure
- Storage in closed original containers

Cleaning Instructions

- Ethanol
- Please clean machine and tools immediately with alcohol. Dried film clean up with TERRAGLOSS CLEAN Cleaning Agent G 13/160.

Regulatory Compliance

- Disclaimer: For regulatory compliances please reach out to your responsible ACTEGA contact person.

Additional Information

It is highly recommended to protect the coating from mechanical damage.

Disclaimer

As características contidas no presente documento constituem especificações vinculantes do produto, as quais garantimos, desde que as condições e métodos de teste aqui mencionados sejam utilizados. Quaisquer outros requisitos subjetivos ou objetivos relacionados aos produtos estão excluídos. Qualquer informação aqui contida sobre adequação, uso ou aplicação dos produtos não é vinculante e não constitui um compromisso em relação às propriedades, uso ou aplicação dos produtos. Sugerimos que faça testes preliminares com nossos produtos para garantir sua adequação à finalidade pretendida antes de utilizá-los. Não garantimos a comercialização ou adequação dos produtos aqui mencionados para qualquer finalidade específica, tampouco que os produtos, os dados e as informações possam ser utilizados sem infringir os direitos de propriedade intelectual de terceiros.