Latest Update / Jan 14, 2025

# Technical Data Sheet STARKOTE® AQ-454

Aqueous high gloss coating

ACTEGA North America, Inc. 1450 Taylors Lane, Cinnaminson, NJ 08077 US +1 800-255-0021 info.ACTEGA.northamerica@altana.com www.actega.com

## **Product Description**

Aqueous high gloss coating, for 1-sided work

| General Information  |   |  |
|----------------------|---|--|
| Product Type         | Coatings  |  |
| Product Technology   | Water based   |  |
| Field Of Application | Publication & Commercial, Advertising, Brochures, Catalogs,<br>Commercial, Displays, Other Specialities       |  |
| Properties           | Good printability, good adhesion, Proves in practice to be suitable as coating for the later counter glueing. |  |

## **Application Method**

• Blanket, Tower, Dampener and Anilox Coaters, 9-11 bcm

### Substrate Recommendation

- Coated Board
- Coated Paper

#### Properties

Gloss Scuff Resistance Hot Foil Stamping Slip Surface Smoothness Counter Glueing

# 

| Product Characteristics |  |                  |                  |
|-------------------------|--|------------------|------------------|
| Viscosity               | • ~ s -1 (15-18) -2 (19-22) -3 (23-26) (#3 Zahn Cup at 23°C) |                  |                  |
| Hot Foil Stamping       |  | Glueability      |                  |
| Drying AQ               | Hot air knives with air evacuation                           | Slip Angle       | 22 +/- 2 degrees |
| Heat Resistance         | 120°F @ 16 hrs @ 2 PSI                                       | Anti Penetration |                  |



Latest Update / Jan 14, 2025

# Technical Data Sheet STARKOTE® AQ-454

Aqueous high gloss coating

ACTEGA North America, Inc. 1450 Taylors Lane, Cinnaminson, NJ 08077 US +1 800-255-0021 info.ACTEGA.northamerica@altana.com www.actega.com

#### Storage Instructions

- Shelf-life 12 months
- Applies to closed original containers at 5°C up to 30°C.
- Protect from frost, heat and sun exposure. Storage may cause a change in viscosity. We recommend to check the viscosity and adjust if necessary with water.

#### **Cleaning Instructions**

• Please clean machine and tools immediately with room temperature water or hot water. In cases where the coating has been left to dry, warm water and INKO Cleaner may be required.

#### Disclaimer

The characteristics contained herein constitute binding product specifications which we warrant provided the conditions and testing methods mentioned therein are used. Any other subjective or objective requirements concerning the products are excluded. Any information herein about suitability, use or application of the products is non-binding and does not constitute a commitment regarding the products' properties, use or application. We recommend that you test our products in preliminary trials to determine their suitability for your intended purpose prior to use. No warranties of merchantability or fitness for a particular purpose are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties.

