

**tds\_header\_technicalDataSheet**

**ULTRASHEEN® UV-378B**

UV curable gloss ink train primer varnish

**ACTEGA North America, Inc.**

1450 Taylors Lane, Cinnaminson, NJ 08077 US

+1 800-255-0021

info.ACTEGA.northamerica@altana.com

www.actega.com

**tds\_header\_productDescription**

UV curable gloss ink train primer varnish, UV coatable and foil stampable

<b>tds_header_generalInformation</b>	
<b>tds_label_productType</b>	prd_type_coatings
<b>tds_label_productTechnology</b>	prd_technology_coaUVCuring
<b>tds_label_fieldOfApplication</b>	prd_markets_pc, prd_endUse_brochures, prd_endUse_catalogs, prd_endUse_commercial
<b>tds_label_properties</b>	prd_prop_theProcessingWithFountainSolutionwetOffsetIsPossible, prd_prop_theVarnishHasALowTendencyToPenetrationOnPaperAndBoard, prd_prop_theCoatingContainsOpticalBrightener, prd_prop_verySuitableForHotFoilStamping, prd_prop_suitabilityOfFoilsmustBeChecked, prd_prop_provesInPracticeToBeSuitableAsCoatingForTheLaterCounterGlueing, prd_prop_provesInPracticeToBeSuitableAsAdhesionPromoterBetweenSubstrate

**tds\_header\_applicationMethod**

- Wet or dry litho via ink train; The recommended coating weight is 0.3 – 0.5 lbs/1000 square feet and the mileage should be similar to that of regular ink varnish

**tds\_header\_substrateRecom**

- prd\_subRec\_coatedBoard
- prd\_subRec\_coatedPaper

tds\_header\_technicalDataSheet

**ULTRASHEEN® UV-378B**

UV curable gloss ink train primer varnish

**ACTEGA North America, Inc.**

1450 Taylors Lane, Cinnaminson, NJ 08077 US

+1 800-255-0021

info.ACTEGA.northamerica@altana.com

www.actega.com

tds\_header\_properties

tds\_label\_gloss

tds\_label\_flexibility

tds\_label\_scuffResistance


tds\_label\_hotFoilStamping

tds\_label\_slipSurfaceSmoothness

tds\_label\_reactivity

tds\_label\_uvVarnishing

tds\_label\_counterGlueing



tds_header_productCharacteristics			
tds_label_viscosity	• ~3,000 mPas +/- 500 (prd_visc_centipoise_40C)		
tds_label_curing	• 100 - 125 fpm @ 300WPI		
tds_label_hotFoilStamping	<input checked="" type="checkbox"/>	tds_label_glueAbilityUV	<input checked="" type="checkbox"/>
tds_label_antiPenetration	<input type="checkbox"/>		

tds\_header\_storageInstructions

- prd\_storageInformation\_shelfLife6Months
- prd\_storageInformation\_closed\_t5to30

tds\_header\_cleaningInstructions

- prd\_clean\_pleaseCleanCommercialCleaningAgents

tds\_header\_additionalInformation

MEK Resistance: 10 - 20 Double Rubs

\* Estimated chemical resistance on press

## tds\_header\_technicalDataSheet

### ULTRASHEEN® UV-378B

UV curable gloss ink train primer varnish

#### ACTEGA North America, Inc.

1450 Taylors Lane, Cinnaminson, NJ 08077 US

+1 800-255-0021

info.ACTEGA.northamerica@altana.com

www.actega.com

## tds\_header\_disclaimer

The characteristics contained herein constitute binding product specifications which we warrant provided the conditions and testing methods mentioned therein are used. Any other subjective or objective requirements concerning the products are excluded. Any information herein about suitability, use or application of the products is non-binding and does not constitute a commitment regarding the products' properties, use or application. We recommend that you test our products in preliminary trials to determine their suitability for your intended purpose prior to use. No warranties of merchantability or fitness for a particular purpose are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties.