

**Technical Data Sheet**  
**ULTRASHEEN® UV-9788A**

UV curable matte scuff resistant coating

ACTEGA North America, Inc.  
 1450 Taylors Lane, Cinnaminson, NJ 08077 US  
 +1 800-255-0021  
 info.ACTEGA.northamerica@altana.com  
 www.actega.com

**Product Description**

UV curable matte scuff resistant coating for web offset

General Information	
Product Type	Coatings
Product Technology	UV curing
Field Of Application	Publication & Commercial, Catalogs, Commercial, Magazines
Properties	Chemical resistance, Good rub and scratch resistance, Good wetting on different printing inks, e. g. conventional, UV printing inks, web offset printing inks, make tests!, Proves in practice to be suitable as coating for the later counter glueing., Proves in practice to be suitable as two-sided coating., Sutherland Rub Resistance, The coating contains optical brightener., Very suitable for hot foil stamping, Suitability of foils must be checked

**Application Method**


- Web Offset, Blanket or Flexo Coaters, 12-14 bcm

**Substrate Recommendation**

- Coated Paper

**Properties**

- Gloss
- Flexibility
- Scuff Resistance
- Slip Surface Smoothness
- Reactivity
- Two Sided Coating
- Counter Glueing



Product Characteristics	
Viscosity	• ~350 mPas +/- 30 (Centipoise at 25°C)

**Technical Data Sheet**  
**ULTRASHEEN® UV-9788A**

UV curable matte scuff resistant coating

ACTEGA North America, Inc.  
 1450 Taylors Lane, Cinnaminson, NJ 08077 US  
 +1 800-255-0021  
 info.ACTEGA.northamerica@altana.com  
 www.actega.com

Product Characteristics			
Curing	• 125 fpm @ 300WPI		
Hot Foil Stamping	<input checked="" type="checkbox"/>	Glueability	<input checked="" type="checkbox"/>
Anti Penetration	<input type="checkbox"/>		

**Storage Instructions**

- Shelf-life 6 months
- Applies to closed original containers at 5°C up to 30°C.

**Cleaning Instructions**

- Please clean machines and tools with commercial cleaning agents.

**Additional Information**

MEK Resistance: 30 - 40 Double Rubs  
 \* Estimated chemical resistance on press

**Disclaimer**

The characteristics contained herein constitute binding product specifications which we warrant provided the conditions and testing methods mentioned therein are used. Any other subjective or objective requirements concerning the products are excluded. Any information herein about suitability, use or application of the products is non-binding and does not constitute a commitment regarding the products’ properties, use or application. We recommend that you test our products in preliminary trials to determine their suitability for your intended purpose prior to use. No warranties of merchantability or fitness for a particular purpose are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties.